

# Willow Technologies Ltd.

Shawlands Court, Newchapel Road, Lingfield, Surrey, RH7 6BL, UK

Tel. + 44 (0) 1342 835234, Fax. + 44 (0) 1342 834306, e-mail [sales@willow.co.uk](mailto:sales@willow.co.uk) web [www.willow.co.uk](http://www.willow.co.uk)

## **Series 60APS 60 Amps**

### **3 POLE**

contactor (normally open) is designed for resistive loads typical in industrial ovens, food processing and laboratory equipment, lighting and computer power supplies, plus medical and communications equipment.

The 60 Amp contactor is UL/CSA listed for general purpose, inductive, and tungsten, as well as resistive loads. The contactor features long life, quiet operation, and rapid on/off cycling. Since it is hermetically sealed, it is a practical replacement, especially in hostile environments.

<b>Maximum Time:</b>	<b>Operate</b>	<b>Release</b>
	70 ms, Max.	90 ms, Max
<b>Contact Bounce:</b>	None	
<b>Recommended DC Load Polarity:</b>	Top Connection Negative	
<b>Breakdown Voltage:</b>		
<b>Contact to Contact:</b>	2000 VRMS/Min.	
<b>Contact to Ground:</b>	5000 VRMS/Min.	



3 Pole (Normally Open)							
Rating	Part No.	Weight (g)	Dimensions (mm)	Dimensions (mm)	Dimensions (mm)	Dimensions (mm)	Dimensions (mm)
120	3060APS120AC	122	9.54	0.224	26.88		
240	3060APS240AC	470	9.47	0.110	26.40		
480	3060APS480AC	1900	10.12	0.055	26.40		
12 (DC)	3060APS12DC	12.8	10.10	0.866	10.39		
24 (DC)	3060APS24DC	46	11.10	0.461	11.06		



# Willow Technologies Ltd.

Shawlands Court, Newchapel Road, Lingfield, Surrey, RH7 6BL, UK

Tel. + 44 (0) 1342 835234, Fax. + 44 (0) 1342 834306, e-mail [sales@willow.co.uk](mailto:sales@willow.co.uk) web [www.willow.co.uk](http://www.willow.co.uk)

## **3 POLE**

