



American Electronic Components, Inc.

1101 Lafayette Street, Elkhart, IN 46516, Tel: (574) 295-6330, Fax: (574) 293-8013, sales@aecsensors.com

DURAKOOL Series BBC (Closed) 60 Amps


2 POLE

The unusually long life of Durakool "B" size contactors in proportional temperature control systems has made them the most popular choice of designers of process heating controls.

BFC (normally open) and BBC (normally closed) contactors are general purpose, 60 Amp rated, featuring mercury-to-tungsten contacts. Tungsten's ability to resist arcing erosion greatly prolongs the life of the contactor. These relays can be used in plastic extrusion equipment to cycle heaters for precise temperature control.

SPECIFICATIONS

Maximum Time: Operate 70 ms Release 90 ms
Normally Open: 70 ms 90 ms
Normally Closed: 120 ms 90 ms
Contact Bounce, Release: None
Recommended DC Load Polarity: Top Connector Negative
Load Connectors: Pressure Connector #1-8 AWG Cu.
Coil Terminals: #6-32 Wire Binding Screw, Max. #12 AWG Cu.
Breakdown Voltage: 5000 VRMS/Min. Across Contacts



DESCRIPTION	Volts	BBC (Normally Closed)			
		Part Number	Typical Coil Data		
			DC Ohms	Watts	Amps
2 Pole	24	BBC2-309	15	5.00	0.510
	120	BBC2-305	350	6.60	0.123
	208	BBC2-310	960	6.30	0.070
	240	BBC2-306	1520	5.40	0.054
	277	BBC2-311	2300	5.50	0.044
	480	BBC2-312	5600	5.60	0.027
	12 (DC)	BBC2-313	24	6.00	0.500
	24 (DC)	BBC2-308	90	6.00	0.250

ELECTRICAL RATINGS	GENERAL PURPOSE 0.7/0.8 UL Power Factor						DC			Tungsten Lamp/60 Hz		AC MOTOR LOAD						
	Volts										120		1 Phase			3 Phase		
		120	208	240	277	480	600	1-48	120	240	120	240	480	120	240	480		
SERIES	60 Hz Amps						DC Amps			Amps	KW	Hp	Hp	Hp	Hp	Hp	Hp	
BFC 60 (Normally Open)	60	60	60	60	60	60	60	30	20	60	7.2	3.0	5.0	7.5	5.0	10.0	15.0	
BBC 60 (Normally Closed)	60	45	45	45	35	25	60	30	20	55	6.6	3.0	5.0	—	5.0	7.5	—	

